



910.782.2477  
www.SoundHM.com

## -7/-11 SERIES STANDARD SPECIFICATIONS

Model	Weight (lbs)	Transport Dimensions (LxWxH) (ft-in)	Net HP	Arm (ft-in)	Max Reach (ft-in)	Max Depth (ft-in)	Lift Capacity Over Front (ft-in)(lbs)	Arm Digging Force (lbf)	Bucket Digging Force (lbf)	Ground Pressure (psi)
SK17SR-6E	3,681	11' 4" x 4' 2" x 7' 7"	15	3' 1"	*12' 3"	7' 3"	7' 6" 1,686	1,911	3,417	4.20
SK26SR-7 Canopy [Cab]	6,195 [6,395]	14' x 5' 1" x 8' 1"	23	4' 7"	16' 6"	9' 2"	10' 0" 1,270 [1,340]	2,790	4,680	4.77 [5.02]
SK35SR-7 Canopy [Cab]	9,250 [9,600]	16' X 5' 7" x 8' 3"	23	5' 6"	18' 6"	10' 9"	10' 0" 3,280	4,380	7,240	5.30 [5.50]
SK45SRX-7 Canopy [Cab]	10,295 [10,648]	17' 4" x 6' 5" x 8' 5"	37	5' 1"	19' 2"	11' 3"	10' 0" 5,580	4,473	6,991	3.80 [3.90]
SK55SRX-7 Canopy [Cab]	11,857 [12,147]	18' 3" x 6' 5" x 8' 5"	37	5' 7"	20' 5"	12' 9"	10' 0" 5,350	5,417	8,003	4.40 [4.50]
SK75SR-7	18,700	20' 10" x 8' x 8' 5"	70	7' 0"	22' 7"	15' 0"	10' 0" 7,990	7,900	15,900	5.28
SK75SR-7 Offset Boom	19,555	20' 10" x 8' x 8' 5"	70	5'9"	21' 3"	14' 1"	10' 0" 8,000	8,860	15,900	5.52
SK85CS-7	20,100	22' 2" x 8' x 8' 5"	70	7' 0"	24' 7"	14' 7"	10' 0" 8,680	7,580	15,900	5.7
SK130LC-11	32,800	25' 7" x 8' 6" x 10' 3"	96	7' 10"	28' 10"	18' 1"	15' 0" 12,620	14,400	24,800	6.20
SK140SRLC-7	32,800 [35,005**]	24' 8" x 8' 6" 10' 3"	105	7' 10"	28' 11"	19' 7"	15' 0" 12,170	14,400	24,800	6.3
SK140SRLC-7 Offset Boom	33,700 [35,905**]	24' 8" x 8' 6" 10' 3"	105	8' 2"	25' 9"	17' 2"	15' 0" 10,290	12,900	22,000	6.5
ED160BR-7	37,000	29' 8" x 8' 6" x 9' 11"	105	9' 4"	28' 11"	19' 0"	15' 0" 12,240	13,000	24,800	6.5
SK170LC-11	39,500	28' 7" x 8' 6" x 10' 2"	123	10' 2"	31' 2"	21' 4"	20' 0" 9,640	17,700	28,300	6.00
SK210LC-11	50,000	31' 6" x 10' 5" x 10'	160	20' 10"	32' 6"	39' 5"	20' 0" 16,660	12,100	19,800	6.2
SK230SRLC-7	57,100	29' x 10' 5" x 10' 4"	164	9' 5"	31' 10"	21' 7"	20' 0" 17,270	21,800	29,700	5.9
SK260LC-11	60,200	33' 6" x 11' 1" x 10' 5"	178	9' 9"	33' 10"	23' 0"	20' 0" 21,080	30,100	42,000	6.6
SK270SRLC-7	61,100	29' 5" x 11' 2" x 10' 5"	164	9' 8"	32' 4"	21' 10"	20' 0" 17,710	25,200	35,300	6.00
SK300LC-11	69,200	35' 2" x 11' 1" x 10' 6"	265	10' 2"	35' 8"	23' 7"	20' 0" 25,110	31,200	46,800	6.5
SK350LC-11	84,200	37' 1" x 11' 1" x 11' 3"	265	10' 10"	36' 11"	24' 1"	20' 0" 34,010	40,700	56,200	7.8
SK380SRLC-7	84,700	32' 9" x 11' 3" x 11' 9"	265	10' 2"	35' 10"	22' 11"	20' 0" 27,540	31,200	46,800	7.8
SK390LC-11	84,657	36' 8" x 12' x 11' 7"	265	10' 10"	39' 3"	23' 1"	20' 0" 32,720	40,700	56,200	9
SK520LC-11	121,000	40' 7" x 11' 11" x 12' 4"	463	11' 4"	39' 7"	25' 6"	20' 0" 46,540	54,400	72,200	9.1

\*Ground Level

7/24/2024

\*\*Optional Bolt-on Counter Weight

Information shown above is based on standard features ONLY. Due to our policy of continuous product improvements all designs and specifications are subject to change without advance notice. For any specific information on specialty equipment please consult your nearest KOBELCO distributor.



910.782.2477

www.SoundHM.com

**-7/-11 SERIES STANDARD EQUIPMENT**

EQUIPMENT	SHORT RADIUS -7							CONVENTIONAL -11							
	SK75SR-7	SK85CS-7	SK140SR-7	ED160BR-7	SK230SR-7	SK270SR-7	SK380SR-7	SK130LC-11	SK170LC-11	SK210LC-11	SK260LC-11	SK300LC-11	SK350LC-11	SK390LC-11	SK520LC-11
4 year / 4000 hour warranty	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes**	Yes	Yes	Yes
Telematics for warranty term	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Overhead Guard Heavy Duty FOPS Level II	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
270 Degree 3-camera system	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Quick Coupler Ready System	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No
Machine Guidance Ready Brackets	No	No	No	No	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
10" Monitor w/ Jog Dial	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Dozer Blade (Float is included)	Yes	Yes	Optional	6 way blade	Optional	Optional	No	Yes	No	No	No	No	No	No	No
Air Ride heated suspension seat	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
iNDR cooling system	Yes	Yes	Yes	Yes	Yes	Yes	No	No	No	No	No	No	No	No	No
N&B 2 way Aux. Hydraulics	No	No	No	No	Yes	Yes	Yes	No	Yes	Yes**	Yes**	Yes**	Yes	Yes	Yes
Combination secondary rotation circuit	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional
LED Lights	5	5	5	5	7	7	7	7	7	7	7	7	7	7	7
Swing Flashers	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Arm Rock Guard Weldment	Yes	Yes	Yes	Yes	No	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Pattern Changer	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Heavy Duty Boom\arm	Yes	Yes	Yes	Yes	No	Yes	Yes	No	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Independent Travel	No	No	Yes	Yes	Yes	Yes	Yes	No	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Heavy Lift	No	No	No	No	Yes	Yes	Yes	No	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Power Boost (Unlimited time)	No	No	No	No	Yes	Yes	Yes	No	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Pre-drilled shoes for rubber pads	Yes	Yes	Yes	No	No	No	No	Yes	Yes	No	No	No	No	No	No
Auto Warm up	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Auto Idle shut down	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
DEF required	No	No	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
SCR only	No	No	Yes	Yes	No	No	Yes	Yes	No	No	No	Yes	Yes	Yes	Yes
DPF only	Yes	Yes	No	No	No	No	No	No	No	No	No	No	No	No	No
DPF with SCR	No	No	No	No	Yes	Yes	No	No	Yes	Yes	Yes	No	No	No	No
Swing Boom	No	Yes	No	No	No	No	No	No	No	No	No	No	No	No	No
Offset boom option	Yes	No	Yes	No	No	No	No	No	No	No	No	No	No	No	No
High and Wide undercarriage Opt	No	No	No	No	No	No	No	No	No	Yes	Yes	No	No	Yes	No
Long Reach Boom & Stick Opt.	No	No	No	No	No	No	No	No	No	Yes - 50'	Yes - 60'	Yes - 62'	No	No	No
Engine Manufacture	Yanmar	Yanmar	Isuzu	Isuzu	Yanmar	Yanmar	Isuzu	Isuzu	Yanmar	Yanmar	Yanmar	Isuzu	Isuzu	Isuzu	Isuzu
Boom to Arm Regeneration	No	No	No	No	No	No	No	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
K-LOAD Payload Weighing ****	No	No	No	No	Yes ****	Yes ****	Yes ****	No	Yes ****	Yes ****	Yes ****	Yes ****	Yes ****	Yes ****	Yes ****
Hydraulic Pressure Release	Yes	Yes	Yes	Yes	Yes *	Yes *	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
10 pre-set Attachment settings	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes

\* Heavy counter weight only on Long Reach  
 \*\* Not available on long reach  
 \*\*\* Running change that varies by serial number.  
 SK300LC-11 Long Reach Warranty is 3Y/3K Hours  
 Offset Machines - No N&B PHC

Information shown above is based on standard features ONLY. Due to our policy of continuous product improvements all designs and specifications are subject to change without advance notice. For any specific information on specialty equipment please consult your KOBELCO District Business Manager.