



# 17.45 BIG RANGE

## TECHNICAL FEATURES

MODELS		17.45
<b>DIMENSIONS</b>		
[A] Height	ft	8.3
[B] Width	ft	7.7
[C] Gauge	ft	6
[D] Ground clearance	ft	1.1
[E] Front overhang	ft	7.6
[F] Pitch	ft	9.6
[G] Rear overhang	ft	4
[H] Width with stabilizers	ft	11.2
[I] Length	ft	21.3
[L] Cabin width	ft	3.1
<b>WEIGHT</b>		
Classic 55	lbs	26,631
Classic 74	lbs	26,786

MODELS		17.45
<b>DETAILS</b>		
Number of extracting sections	nr	3
Max capacity	lbs	9,920
Max lifting height	ft	53.8
Max horizontal boom extension	ft	41.3
Boom extension at max height	ft	8.2
Swinging Angle	°	144
<b>TANK CAPACITY</b>		
Hydraulic oil tank	gal	39.6
Diesel tank	gal	31.7
<b>CONNECTION FOR EQUIPMENT</b>		
FH		●
EURO		○

Dimensions defined on model with wheels 405/70 20

CONFIGURATION		CLASSIC 55	CLASSIC 74
<b>TRANSMISSION</b>			
Hydrostatic		single gear	single gear
Speed	mph	15.5	18.6
<b>ENGINE TIER 4 FINAL</b>			
Builder		Deutz Tier 4 Final	Deutz Tier 4 Final
Power	kW/hp	55,4/75,3	74,4/101
Aftertreatment system		DOC + DPF	DOC + DPF + SCR
Drawbar pull	daN	5000	5000
<b>HYDRAULIC</b>			
Pump type		gears pump	gears pump
Hydraulic capacity	gal/psi	31.7/3,335	31.7/3,335
<b>TYRES</b>			
405/70 20		●	●
405/70 24		○	○
445/65 R22.5*		○	○
Turning radius	ft	13.8	13.8
<b>OTHER</b>			
Joystick		mechanical-electro proportional	mechanical-electro proportional
Quick coupling		○	○
Electro-proportional double acting rear hydraulic connection		○	○
Front and rear LED lights		○	○
Rear trailer lights socket		○	○
6 t fixed tow hook		○	○
Engine water pre-heating		○	○
Air conditioning		○	○
Floating boom		○	○
Boom suspension		○	○
Manual 6-way diverter		○	○
PEB (Boom Electric Socket)		○	○
Creeper		○	○
Front constant flow		○	○
Bucket mode		●	●
Pneumatic / hydraulic trailer brake		○	○
Frame lateral levelling ±10°		●	●
Front Stabilizers		●	●
Rear axle swing block		○	○

\* standard on models 17.45

● Standard

○ Optional

- Not available